2024 CAN-AM COMMANDER XT 1000R



PACKAGE HIGHLIGHTS

- 28 in. XPS Trail King tyres
- 64 in. wide with high clearance Arched A-Arms
- 7.6 in. digital display with keypad
- · Can-Am LED signature lights
- · 14 in. cast-aluminium wheels
- XT front bumper
- 4,500 lb (2,041 kg) winch
- Full roof
- · Premium half doors
- Puncture resistant 8 ply tyres
- D.E.S.S. $^{\text{\tiny{TM}}}$ Key with speed limiting capabilities
- Full Skid Plate
- Rear Differential with Turf mode
- · Sport Performance with Utility style tipping tray

Triple Black

ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok† auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS™)
SUSPENSIONS Front Suspension	Arched double A-arm with sway bar/12.5 in. (31.8 cm) travel
Front Shocks	Twin tube gas-charged shocks
Rear Suspension	Arched TTA with sway bar/15 in. (38.1 cm) travel
Rear Shocks	Twin tube gas-charged shocks
TYRES & WHEELS	
Front Tyres	XPS Trail King 28 x 9 x 14 in.
Rear Tyres	XPS Trail King 28 x 11 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 220mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,675 lb (759.8 kg)	
Chassis/Cage	Profiled cage, ROPS approved	
LxWxH	130 x 64 x 74 in. (330.2 x 162.6 x 188 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	13 in. (33 cm)	
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)	
Cargo Box Capacity	600 lb (272.2 kg)	
Towing Capacity	2,000 lb (907.2 kg)	
Payload Capacity	1,030 lb (467.2 kg)	
Storage Capacity	Total: 7.3 gal (27.6 L)	
Fuel Capacity	10 gal (38 L)	
Person Capacity	2	

FEATURES

ıge 7.6	in. wide digital display with keypad
trumentation DC	Coutlet (10-A)
	Digitally Encoded Security System (D.E.S.S.™) th Start/Stop button
gneto 65	0 W
LE	ont lighting output 110 W D signature lights D tail lights
nch 4,5	600-lb (2,041 kg) winch with roller fairlead
ering Wheel Ad	justable tilt steering
Fu Mı XT	emium half doors Il skid plate udguards front bumper Il roof
ch Type 2 i	n. hitch receiver
tection Pre Fu Mu XT Fu	emium half doors Il skid plate Idguards front bumper Il roof

WARRANTY

Factory Warranty	3-year unlimited km powertrain & Rotax® engine warranty and
	1-year warranty & unlimited km on the rest of the unit



